

Precision Low Power Waveguide Terminations

SPECIFICATIONS

MODELS	Frequency Range (GHz)	Waveguide Size	Flange	Power Ave. Max (Watts)	VSWR
WT430	1.70 - 2.60	WR430	UG437B/U	10	1.15:1
WT340	2.10 - 3.00	WR340	UG437B/U	10	1.05:1
WT284	2.65 - 3.95	WR284	UG584/U	5	1.05:1
WT229	3.30 - 4.90	WR229	CMR229	5	1.05:1
WT187	3.95 - 5.85	WR187	UG407/U	5	1.05:1
WT159	4.90 - 7.05	WR159	CMR159	4	1.05:1
WT137	5.85 - 8.20	WR137	UG441/U	3	1.05:1
WR112	7.05 - 10.00	WR112	UG138/U	2	1.05:1
WR90	8.20 - 12.40	WR90	UG135/U	2	1.05:1
WR75	10.00 - 15.00	WR75	M3922/53-008	2	1.05:1
WR62	12.40 - 18.00	WR62	UG1665/U	1.5	1.05:1
WR42	18.00 - 26.50	WR42	UG595/U	1.5	1.05:1
WR28	26.50 - 40.00	WR28	UG599/U	1.0	1.05:1