

Short Length-Low Power Waveguide Terminations

SPECIFICATIONS

MODELS	Frequency Range (GHz)	Waveguide Size	Flange	Ave. Power Max (Watts)	VSWR	Length (inches)
WST430	1.70 - 2.60	WR430	UG437B/U	10	1.15:1	3.00
WST284	2.65 - 3.95	WR284	UG584/U	5	1.15:1	2.50
WST229	3.30 - 4.90	WR229	CMR229	5	1.15:1	2.25
WST187	3.95 - 5.85	WR187	UG407/U	5	1.15:1	2.00
WST159	4.90 - 7.05	WR159	CMR159	4	1.15:1	1.75
WST137	5.85 - 8.20	WR137	UG441/U	3	1.15:1	1.50
WST112	7.05 - 10.00	WR112	UG138/U	2	1.15:1	1.00
WST90	8.20 - 12.40	WR90	UG135/U	2	1.15:1	1.00
WST75	10.00 - 15.00	WR75	M3922/53-008	2	1.15:1	.75
WST62	12.40 - 18.00	WR62	UG1665/U	1.5	1.15:1	.75
WST42	18.00 - 26.50	WR42	UG595/U	1.5	1.15:1	.75
WST28	26.50 - 40.00	WR28	UG599/U	1.0	1.15:1	.75

Note: Improved VSWR available over narrower bandwidths. Other flange types available upon request.